EQUIPMENT DETAILS

1999 CHEVROLET S-10 LS

The information below was known to be true at the time the vehicle was manufactured. The vehicle's current condition may mean that a feature described below is no longer available on the vehicle. This data should be used along with images, condition data and further inspection to assess value before making a decision about the vehicle.

Factory Options

ADDITIONAL OPTIONS

15" x 7" CAST-ALUMINUM ARGENT WHEELS
AUX FRONT FLOOR MATS
COMFORT CONVENIENCE PKG; -inc: tilt wheel, speed control
DEEP TINTED GLASS; *rear window is light tinted w/A28 Window*
TACHOMETER

AXLE

BODY CODE

FLEETSIDE BODY

DECOR

LS DECOR; -inc: *Contents listed in STD Equipment*

EMISSIONS

FEDERAL EMISSIONS

ENGINE

2.2L (134) SFI L4 (VORTEC) ENGINE 4 Cylinder Engine

GVWR

4200# GVWR; (2500 front/2300 rear), springs (2500 front/2300 rear), axles (2500 front/ 2900 rear)

PAINT

SOLID PAINT

PREFERRED EQUIPMENT GROUP

PREFERRED EQUIPMENT GROUP; -inc: LS decor, ETR AM/FM stereo w/cassette, air cond,front floor mats, aluminum wheels

SEAT TRIM

DELUXE CLOTH TRIM Cloth Seats

SEAT TYPE

60/40 RECLINING SPLIT BENCH SEAT; -inc: folding backrest, armrest w/integral storage, dual cupholders

SUSPENSION PKG

SMOOTH SUSPENSION PKG; (ride: solid/smooth); (road use: paved)

TIRES

P205/75R15 ALL-SEASON SBR BSW TIRES

TRANSMISSION

5-SPEED MANUAL TRANSMISSION W/OD 5-Speed M/T M/T

Equipment Details

MECHANICAL

(4) Load tie-down anchors
100 amp alternator
19 gallon fuel tank
2.2L (134) SFI L4 (Vortec) engine
4200# GVWR (2500 front/2300 rear), springs (2500 front/2300 rear), axles (2500 front/2900 rear)

Front stabilizer bar
HD 525 CCA battery w/rundown protection
Independent front suspension w/coil springs
Multi-leaf spring rear suspension
Pwr front disc/rear drum brakes
Pwr steering
Rear wheel drive
Semi-floating rear axle
Spare tire carrier mounted under bed
Stainless steel exhaust system
Tools-inc: jack w/cover & wheel wrench

Welded double-wall construction in box sides/tailgate w/steel floor

EXTERIOR

"LS" badge on "B" pillar
Adjustable intermittent windshield wipers
Body-color air dam
Body-color front/rear-step bumpers
Chrome & gray grille
Dual black below-eye-line mirrors
Halogen composite headlamps
Insulation-inc: dash panels, doors, cab back, floor, hood, instrument panel, cowl/fender seal
Solar-Ray tinted glass
Solid exterior paint

INTERIOR

Back panel carpeting

Day/night rearview mirror
Deluxe black 4-spoke steering wheel
Dual coat hooks
Dual covered pwr points
Dual padded armrests integral w/door panels
Dual padded color-keyed cloth sunshades w/LH map strap, RH vanity mirror
Full-coverage, foam-backed, color-keyed cloth headliner
Full-floor color-keyed carpeting
Glove box w/door-operated light

Headlamp-on/turn-signal reminder warning buzzers Heater/defogger w/side window defoggers

Instrument panel cigarette lighter w/ashtray light

Instruments-inc: speedometer, odometer, trip odometer, fuel/voltmeter/temp/ oil pressure gauges

Lights-inc: door-operated dome & front floor courtesy w/delayed entry

Molded door trim panels w/dual map pockets, soft cloth upper insert

Passenger assist handle

Passlock theft deterrent security system

Retained accessory power

Scotchgard fabric protector on cloth trim/door panels, carpeting

SAFETY

Color-keyed manual lap safety belt, center seat position Color-keyed manual lap/shoulder safety belts, outboard seat positions Driver & front passenger airbags w/passenger suppression switch on instrument panel Dual note horn Energy-absorbing steering column Side door guard beams

Vehicle Equipment

AIR BAG - FRONTAL

Driver Air Bag Passenger Air Bag Passenger Air Bag On/Off Switch

AIR CONDITIONING

A/C

AUDIO

AM/FM Stereo

BRAKES

ABS

Front Disc/Rear Drum Brakes

CONVENIENCE

Automatic Headlights
Cruise Control
Engine Immobilizer
Intermittent Wipers
Power Outlet
Variable Speed Intermittent Wipers

Rear Wheel Drive	
Real Wileel Diffe	
ENGINE	
2.2L (134) SFI L4 (VORTEC) ENGINE	
4 Cylinder Engine	
FLOOR MATS	
Floor Mats	
FUEL	
Gasoline Fuel	
SAFETY FEATURES	
SAFETY FEATURES Daytime Running Lights	
Daytime Running Lights	
Daytime Running Lights SEAT TRIM DELUXE CLOTH TRIM	
Daytime Running Lights SEAT TRIM	
SEAT TRIM DELUXE CLOTH TRIM Cloth Seats	
Daytime Running Lights SEAT TRIM DELUXE CLOTH TRIM	
SEAT TRIM DELUXE CLOTH TRIM Cloth Seats	

TIRE - FRONT

Tires - Front All-Season

TIRE - REAR

Tires - Rear All-Season

TRANSMISSION

5-SPEED MANUAL TRANSMISSION W/OD 5-Speed M/T M/T

WHEELS

Aluminum Wheels

WINDOW

Privacy Glass

Technical Specifications

CHASSIS

Brake Type - Power N/A
Disc - Front (Yes or) - Yes N/A
Drum - Rear (Yes or) - Yes N/A
Front Brake Rotor Diam x Thickness - 10.5 x 1.03 in
Rear Drum Diam x Width - 9.5 x 2.0 in

Frame Type - Ladder N/A

Fuel Tank Capacity, Approx - 19 gal Fuel Tank Location - Inboard LH Frame N/A

Steering Ratio (:1), At Lock - 13 N/A Steering Ratio (:1), On Center - 15 N/A Steering Type - Power N/A Turning Diameter - Curb to Curb - 36.9 ft Turning Diameter - Wall to Wall - 38.9 ft

Axle Capacity - Front - 2500 lbs
Axle Capacity - Rear - 2900 lbs
Axle Ratio (:1) - Rear - 3.73 N/A
Axle Type - Rear - Semi-Floating N/A
Shock Absorber Diameter - Front - 32 mm
Shock Absorber Diameter - Rear - 32 mm
Spring Capacity - Front - 2500 lbs
Spring Capacity - Rear - 2300 lbs
Stabilizer Bar Diameter - Front - 0.98 in
Stabilizer Bar Diameter - Rear - in
Suspension Type - Front - Indep Coil Spring N/A
Suspension Type - Rear - 2-Stage Multi-Leaf N/A

Front Tire Capacity - 1452 lbs
Front Tire Order Code - QCE N/A
Front Tire Size - P205/75R15 N/A
Rear Tire Capacity - 1452 lbs
Rear Tire Order Code - QCE N/A
Rear Tire Size - P205/75R15 N/A
Revolutions/Mile @ 45 mph - Front - 768 Rev/Mile
Revolutions/Mile @ 45 mph - Rear - 768 Rev/Mile
Revolutions/Mile @ 45 mph - Spare - Rev/Mile
Spare Tire Capacity - Ibs

Dead Weight Hitch - Max Tongue Wt. - 350 lbs Dead Weight Hitch - Max Trailer Wt. - 2000 lbs Fifth Wheel Hitch - Max Trailer Wt. - 2000 lbs Wt Distributing Hitch - Max Tongue Wt. - 750 lbs Wt Distributing Hitch - Max Trailer Wt. - 2000 lbs Curb Weight - Front - 1744 lbs Curb Weight - Rear - 1271 lbs Gross Axle Wt Rating - Front - 2500 lbs Gross Axle Wt Rating - Rear - 2300 lbs Gross Combined Wt Rating - 5000 lbs Gross Vehicle Weight Rating Cap - 4200 lbs

Front Wheel Material - Aluminum N/A Front Wheel Size - 15 x 7 in Rear Wheel Material - Aluminum N/A Rear Wheel Size - 15 x 7 in Spare Wheel Material - Steel N/A

DIMENSIONS

Cargo Box (Area) Height - 17.1 in Cargo Box Length @ Floor - 72.8 in Cargo Box Width @ Floor - 54.9 in Cargo Box Width @ Top, Rear - 54.9 in Cargo Box Width @ Wheelhousings - 40.3 in Cargo Volume - 39.4 ft³ Tailgate Width - 54.9 in

Cab to Axle - 37.4 in
Cab to End of Frame - 72.8 in
Front Bumper to Back of Cab - 105.5 in
Ground Clearance, Front - 9.1 in
Ground Clearance, Rear - 7.2 in
Ground to Top of Load Floor - 25.9 in
Height, Overall - 62.0 in
Length, Overall w/o rear bumper - 190.1 in
Overhang, Front - 34.6 in
Overhang, Rear w/o bumper - 47.2 in
Wheelbase - 108.3 in
Width, Max w/o mirrors - 67.9 in

Front Head Room - 39.5 in Front Hip Room - 53.6 in Front Leg Room - 42.4 in Front Shoulder Room - 56.9 in Passenger Capacity - 3 N/A

POWERTRAIN

Total Cooling System Capacity - 11.5 qts

Cold Cranking Amps @ 0° F (Primary) - N/A Maximum Alternator Capacity (amps) - 100 N/A Maximum Alternator Watts - 1200 N/A

Displacement - 2.2L/134 N/A
Engine Order Code - LN2 N/A
Engine Type - Gas L4 N/A
Fuel System - SFI N/A
SAE Net Horsepower @ RPM - 120 @ 5000 N/A
SAE Net Torque @ RPM - 140 @ 3600 N/A

EPA Fuel Economy Est - City - 23 MPG EPA Fuel Economy Est - Hwy - 29 MPG

Clutch Size - 9.13 in
Drivetrain - Rear Wheel Drive N/A
Fifth Gear Ratio (:1) - 0.83 N/A
First Gear Ratio (:1) - 3.94 N/A
Fourth Gear Ratio (:1) - 1.00 N/A
Reverse Ratio (:1) - 3.65 N/A
Second Gear Ratio (:1) - 2.37 N/A
Third Gear Ratio (:1) - 1.49 N/A
Trans Description Cont. - Manual w/OD N/A
Trans Order Code - MW2 N/A
Trans Type - 5 N/A

SUMMARY

Body Code - E63 N/A

Body Style - Reg Cab 6' Fleetside LS N/A Vehicle Name - Chevrolet S-10 N/A

VEHICLE

Country of Origin - United States Chevrolet Trucks